

STANDARD INFORMATION

Standard: UL 1026
Standard ID: Household Electric Cooking and Food Serving Appliances [UL 1026:2012
Ed.6+R:06Jun2019]
Previous Standard ID: Household Electric Cooking and Food Serving Appliances [UL 1026:2012
Ed.6+R:17Jul2018]

EFFECTIVE DATE OF NEW/REVISED REQUIREMENTS

Effective Date: September 1, 2022

IMPACT, OVERVIEW, AND ACTION REQUIRED

Impact Statement: Per our accreditation, Intertek is required to review reports against the standard revisions to confirm compliance. Once compliance is confirmed, the standard reference in the report is updated to show continued compliance to the technical requirements of the standard.

Overview of Changes: Revision of requirements for multiple supply cords. Specific details of new/revised requirements are found in table below.

Current Listings Not Active? – Please immediately identify any current Listing Reports or products that are no longer active and should be removed from our records. We will do this at no charge as long as Intertek is notified in writing prior to the review of your reports.



STANDARD INFORMATION

CLAUSE	VERDICT	COMMENT
		Additions to existing requirements are <u>underlined</u> and deletions are shown lined out below.
10	Info	Supply Connections
10.2	Info	Cord-connected appliances
10.2.1	Info	General
10.2.1.4		In the case of a broiler attachment intended for use on a roaster, a detachable power supply cord acceptable for the purpose shall be supplied with the roaster, and no additional detachable power-supply cord shall be provided with either the roaster or the broiler.
		An appliance with multiple supply connections, or an appliance and any of its accessories provided with independent supply connections, shall not exceed the rating of the intended branch circuit supply under simultaneous operation. See also 10.1.2.1. Any markings and instructions regarding using separate branch circuits shall be disregarded. Both sources of supply shall be considered to be on the same branch circuit.
		Exception No. 1: Not applicable to an appliance with multiple sources of supply, or an appliance and each accessory with independent sources of supply, if provided with a single detachable power-supply cord acceptable for the purpose. No additional detachable power-supply cord shall be provided with either the appliance or the accessory.
		Exception No. 2: Not applicable to accessories that comply with all requirements on this Standard independently. Tests are performed with the accessory placed on the supporting surface and not on the appliance.